



WIRE DIAGRAM

| P1 | P2 |
|----|--------------|
| 1 | 1 (VBUS) |
| 2 | 2 (DATA-) |
| 3 | 3 (DATA+) |
| 4 | 4 (GND) |
| 5 | 5 (SSRX-) |
| 6 | 6 (SSRX+) |
| 7 | 7 (GND_DRIN) |
| 8 | 8 (SSTX-) |
| 9 | 9 (SSTX+) |
| 10 | 10 (SHELL) |

Technical Data

| | |
|-----------------------|----------------------------|
| Voltage Rating | : 30 V/AC max. |
| Current Rating | : 1Amp max. |
| Contact Resistance | : 2.0Ohm max |
| Insulate Resistance | : 10M Ohm/300 V/DC / 0.01S |
| Withstand Voltage | : 100V/AC |
| Operating Temperature | : -20°C ~ 85°C |
| Storage Temperature | : 0°C ~ 80°C |
| Operating Humidity | : 5 ~ 95%RH |
| Storage Humidity | : 10~90%RH |

Title: USB 3.0 Terminal Adapter

| | | | | | | |
|---|-----------|--------------------------|----------|------------|-------|-----|
| GENERAL TOLERANCE X.X ±0.25 X.XX ±0.15 X.XXX ±0.05 ANGLE TOLERANCE ± 1° RADIUS ± 0.25 HOLE ± 0.13 | Part. no. | 515-4-8160 | DRAWN | Wang Pang | UNIT | mm |
| | Item. | USB 3.0 Terminal Adapter | CHECKED | Jade Xu | SIZE | A4 |
| | | | APPROVED | Camily Pun | SCALE | 1:1 |



 **Sugo Industrial Company Limited**
 Tel: 852 27901280 Fax.:852 23890688
 email: sales@sugo.com.hk
 **Sugo International Pty. Limited**
 Tel: (61) 02 8385 0076
 email: sales@sugo-au.com