



Specifications:

- Current rating: 1.0A AC/DC
- Voltage rating: 100V AC/DC
- Contact resistance: 15m ohm. max.
- Insulator resistance: 5000M ohm. Min.
- Withstanding voltage: 1000V AC for one minute
- Operating temperature range: -40°C to +105°C
- Material and Finish:
- Insulator: PBT (UL94V-0)
- Standard Color: Black
- Contact: Beryllium Copper (Becu) Gold Plated
- Sleeve Barrel: Copper Alloy Tin Plated

No. of Positions	DIM'A'	DIM'B'
6	7.62	5.08
8	10.16	7.62
10	12.70	10.16
14	17.78	15.24
16	20.32	17.78
18	22.86	20.32
20	25.40	22.86
24	30.48	27.94
28	35.56	33.02
32	40.64	38.10
40	50.80	48.26
48	60.96	58.42

P.C.B LAYOUT

DATE	REVISION	APPROVAL BY	DIMENSION	mm	DRAW No	
			DRAW BY	Alexander	PART No	IC01-XXP-LP
			APPROVAL BY	Ritki	NAME	LOW PROFILE IC SOCKET
			DATE		SUGO INDUSTRIAL CO., LTD. TEL : 852-27901280 FAX : 852-23890688 Email : sales@sugo.com.hk	