



Contact	A±0.2	B±0.2	C±0.1	D±0.1	E±0.2	Insertion Force	Withdrawal Force
						Unit: lbs (Max.)	Unit: lbs (Min.)
20	15.66	15.66	5.08	5.08	17.28	13	1.1
28	18.20	18.20	7.62	7.62	20.87	15	1.1
32	20.74	18.20	10.16	7.62	23.15	15	1.5
44	23.28	23.28	12.70	12.70	28.05	19	2.8
52	25.82	25.82	15.24	15.24	31.65	22	3.5
68	30.90	30.90	20.32	20.32	38.83	26	5.0
84	35.98	35.98	25.40	25.40	46.00	33	6.0

SPECIFICATIONS

Current Rating: 1A
 Capacitance: 1.0 Picofarads Max.
 Contacts Resistance: 30 Milliohms Max.
 Insulation Resistance: 1000 Megohms Min.
 Withstanding Voltage: AC 600V RMS
 Temperature Range: -50°C To +105°C
 Insulator: Hi-temp PPS, UL 94V-0, Brown
 Contact Material: Phosphor Bronze,
 150u" Tin Over 40u" Nickel
 Durability: 25 Cycles

DATE	REVISION	APPROVAL BY	DIMENSION	mm
			DRAW BY	Alexander
			APPROVAL BY	Ritki
			DATE	

DRAW No	
PART No	PLCC-XXD01
NAME	IC Socket PLCC Type
SUGO INDUSTRIAL CO., LTD.	
TEL : 852-27901280 FAX : 852-23890688	
Email : sales@sugo.com.hk	